# DuPont™ Tychem® 5000

## Heavy-duty protection against chemical hazards




- Strong and durable garments with broad chemical barrier
- Composed of a multi-layer barrier film laminated to a durable fabric
- Provides at least 30 minutes of protection against >145 chemicals
- Tan for discretionary purposes and features a low-visibility patch
- Tychem® 5000 garments are typically used in chemical handling, hazmat, law enforcement, and domestic preparedness applications

Please visit our free online DuPont™ SafeSPEC™ selector tool to determine the most appropriate protection based on your hazard risk assessment.

**safespec.dupont.com**

**Chemical & petrochemical handling**

**Hazardous materials & waste cleanup**

**Industrial hazmat teams**

**Law enforcement**


**Hospitals**

**Fire departments**

**Utilities**

*See next page for additional garment styles and sizes.

| Part number | Garment style | Seam construction | Color | Sizes |
|---|---|---|---|---|
| C3125TTNXX000600 | Coverall with elastic wrists and ankles | Taped | Tan | SM-7X |
| C3127TTNXX000600 | Hooded coverall with elastic wrists and ankles | Taped | Tan | SM-7X |
| C3128TTNXX000600 | Respirator-fit hooded coverall with elastic wrists, attached socks, and outer boot flaps with elastic | Taped | Tan | SM-5X |
| C3184TTNXX000600 | HD design hooded coverall with attached gloves, attached socks, outer boot flaps, and double storm flap with hook-and-loop closure | Taped | Tan | SM-4X |
| C3185TTNXX000600 | HD design respirator-fit hooded coverall with attached gloves, attached socks, outer boot flaps, and double storm flap with hook-and-loop closure | Taped | Tan | SM-4X |
| C3275TTNXX000600 | Long-sleeved apron with bound snap neck, waist ties, and elastic wrists | Taped | Tan | SM-4X |
| C3360TTNXX000600 | Bib overall | Taped | Tan | SM-4X |
| C3525TTNXX000600 | Front-entry encapsulated Level B suit with elastic wrists and ankles, flat back, and one exhaust vent | Taped | Tan | SM-4X |
| C3526TTNXX000600 | Rear-entry encapsulated Level B suit with elastic wrists, attached socks, outer boot flaps, flat back, and one exhaust vent | Taped | Tan | SM-4X |
| C3528TTNXX000600 | Rear-entry encapsulated Level B suit with elastic wrists, attached socks, outer boot flaps, expanded back, and two exhaust vents | Taped | Tan | SM-4X |
| C3651TTNXX000600 | Hood | Taped | Tan | One size fits most |
| C3670TTNXX000600 | Jacket | Taped | Tan | SM-4X |
| C3670TTNXX0006JF | Jacket with CPE sleeve cuff and jam fit glove insert | Taped | Tan | SM-4X |
| C3750TTNXX000600 | Combo suit (jacket and bib overall) | Taped | Tan | SM-4X |




### DuPont™ SafeSPEC™—we're here to help

Our powerful web-based tool can assist you with finding the appropriate DuPont garments for chemical, controlled environment, thermal and mechanical hazards.

**safespec.dupont.com**



### Certified Industrial Hygienist team

A DuPont Certified Industrial Hygienist can conduct a job hazard assessment to help you determine the best DuPont garment for a specific hazard.

** WARNING: Most Tyvek®, ProShield®, and Tychem® garments, should not be used around heat, flames, sparks or in potentially flammable or explosive environments.
Do not knowingly enter an environment in which the concentration of flammable gas is within flammable or explosive limits when wearing a Tychem® 5000 garment. Retreat immediately if you encounter such an environment.
Tychem® 5000 garments are not intended for firefighting activities, nor for protection from hot liquids, steam, molten metals, welding or thermal radiation.
NOTE: Garments should have slip-resistant or anti-slip materials on the outer surface of boots, shoe covers or other garment surfaces in conditions where slipping could occur. Some Tychem® garments have attached socks made of the garment material. These attached socks must be worn inside protective outer footwear and are not suitable as outer footwear. These attached socks do not have adequate durability or slip resistance to be worn as the outer foot covering.

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience become available. It is the user's responsibility to determine the level of toxicity, and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. This information is intended for use by persons having the technical expertise to undertake evaluation under their own specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first check that the garment selected is suitable for the intended use. The end-user should discontinue use of garment if fabric becomes torn, worn or punctured, to avoid potential chemical exposure. Since conditions of use are beyond our control, DUPONT DE NEMOURS, INC. AND ITS AFFILIATES MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THESE PRODUCTS OR INFORMATION. This information is not intended as a license to operate under or a recommendation to infringe any trademark, patent or technical information of DuPont or other persons covering any material or its use.

© 2026 DuPont. All rights reserved. DuPontTM, the DuPont Oval Logo, and all trademarks and service marks denoted with TM, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.

DUPONT™ | DuPont™ SafeSPEC™

**DuPont Personal Protection**
**safespec.dupont.com**
**dpp.dupont.com**

**DuPont Personal Protection**
**DuPont™ Tyvek®**